

BHG 360 Li-Ion**Declaration of independence for hot air**

STEINEL gives you mobility: With its powerful li-ion rechargeable battery, the cordless version of the practical HG 350 S provides ultimate freedom of movement for hot-air applications – even at places without mains power. The formidable 36-volt li-ion power pack that drives the BHG 360 Li-Ion has a capacitance of 2600 mAh and delivers the energy for 15 minutes of unrestricted hot-air work. It has no memory effect and impresses with minimal self-discharge. As a result, this hot air tool - which provides the same temperature stages at its mains-powered counterpart - is immediately ready for operation even after a prolonged period out of use.

The charger supplied with the tool recharges the battery to 75% capacity in just 30 min and to full charge in 60 min.

Features

- Lightweight, ergonomically optimised hot air tool
- Integrated LED light
- Integrated ring for hanging the tool
- Soft grip handle
- Thermal cut-out
- ESD-safe: suitable for use at places where there is a risk of electrostatic discharge
- "Thermo-Signal" temperature indicator

Setting capabilities

- Three-stage switch for setting OFF/COLD/HOT



Ideal for de-soldering electronic components



With optional reflector nozzle, ideal for shrinking cable sleeves



Conveniently positioned control switch for setting OFF / COLD / HOT



The ergonomically shaped soft grip handle ensures comfortable handling



The LED light always provides bright illumination in the work area and also serves as a telltale lamp



With its hanging ring, the BHG 350 Li-Ion is always in easy reach in extreme work situations



Optimised weight balance ensures fatigue-free working

BHG 360 Li-Ion

Prod. No.

Dimensions (h x w x d)

Voltage

Output

Temperature

Airflow rate

Run time

Charger

Charging time

Weight

Accessories

351052 Case

240 x 65 x 265 mm

36 V, rechargeable li-ion battery

300 W

400 °C without nozzle / 500 °C with 7 mm reduction nozzle (included)

100 l/min.

15 min.

LS-36 V

2.6 Ah 30 min (75%) 60 min. (100%)

approx. 1790 g (including rechargeable battery)

7 mm reduction nozzle included

Reduction nozzle with reflector guard

Precision reflector nozzle

10 mm reflector nozzle

40 mm reflector nozzle

Solder shrink sleeve kit

Subject to technical modifications

Prod. No. 077358

Prod. No. 077457

Prod. No. 077556

Prod. No. 077655

Prod. No. 076719

